

**MATERIAL SAFETY
DATA SHEET**

Peace Modern Town C-2408, Dalian, 116023, China
Tel: +86-411-84377919 Fax: +86-411-84511565
Web: www.sibond.com E-mail: info@sibond.com

NAME USED ON LABEL: DIPHENYLDIMETHOXYSILANE
CHEMICAL NAME: DIPHENYLDIMETHOXYSILANE
SYNONYMS: DIMETHOXYDIPHENYLSILANE
CHEMICAL FAMILY: ORGANOSILANE
FORMULA: C₁₄H₁₆O₂Si
HMIS CODES HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	ACGIH
DIPHENYLDIMETHOXYSILANE	6843-66-9	>95	not established

TLV OSHA PEL
not established
(methanol TWA: 200ppm)

PHYSICAL DATA

Boiling Point: 161°C at 15mm	Freezing Point: <0°C
Specific Gravity: 1.077	Vapor Pressure, 25°: <1mm
Vapor Density (air=1): >1	Solubility in water: insoluble, reacts
% volatiles: NA	Evaporation rate: NA
Molecular Weight: 244.36	Other: NA
Appearance & Color: Clear to straw liquid with mild odor	

FIRE & EXPLOSION DATA

Flash Point, COC: 121°C (250°F) Autoignition Temp.: not determined
Flammability Limits: not determined
Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.
Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.
Recommended Disposal: May be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

- 1-

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010

On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.

Eye Contact: Will cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates of may irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity: not determined

Chronic Toxicity: There are no known chronic effects related to this compound.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention, preferably from an ophthalmologist.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

REACTIVITY DATA

Stability: Stable in sealed containers.

Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Reacts with water and moisture in air liberating methanol.

Hazardous decomposition products: Organic Acid Vapors, methanol.

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor acid gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers.

TRANSPORTATION

- 2 -

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010

DOT SHIPPING NAME: CHEMICALS, NOI
DOT HAZARD CLASS: Not Regulated
DOT LABEL: Not Required
DOT ID No: Not Required

The information contained in this document has been gathered from reference materials and/or Sibond test data and is to the best knowledge and belief of Sibond accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Sibond makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

- 3-

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemical Abstract Service Registration Number
Sibond © 2010