

**BREWER SCIENCE INC.
SAFETY DATA SHEET**

This Safety Data Sheet has been prepared to comply with the EC Directive, Canadian WHMIS and the OSHA Hazard Communication Standard.

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION
AND THE COMPANY/UNDERTAKING**

Product Name: ProTEK®B3 Primer

Manufacturer: Brewer Science, Inc.
2401 Brewer Drive
Rolla, MO 65401

Information Phone Number: (573) 364-0300 **Fax:** (573) 368-3318

Email: msds@brewerscience.com

Emergency Phone Number:
Chemtrec Domestic North America: 800-424-9300
Chemtrec International: 703-527-3887

MSDS Date of Preparation: 8/28/07

Product Use: Primer

SECTION 2: HAZARDS IDENTIFICATION

Liquid with a solvent odor.

EMERGENCY OVERVIEW: Flammable liquid and vapor. May cause eye, skin, and respiratory irritation. May cause headache, dizziness, nausea and other symptoms of central nervous system depression.

EU Preparation Classification (1999/45/EC): Flammable R10

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS# / EINECS#	%	EU Classification (67/548/EEC)
1-Methoxy-2-propanol (Propylene glycol monomethyl ether, PGME)	107-98-2 / 203-539-1	95-100	R10
Additive	Proprietary	<1	C R22, R34
Deionized Water	7732-18-5 / 231-791-2	<1-5	Not Applicable

See Section 16 for further information on EU Classification.

SECTION 4: FIRST AID MEASURES

Eye: Rinse thoroughly with water for at least 15 minutes, holding the eye lids open to be sure the material is washed out. Get immediate medical attention.

Skin: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

Inhalation: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Keep the victim calm and warm. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media: Use water fog or spray, alcohol foam, carbon dioxide or dry chemical.

Prepared By:	Safety & Environmental Units
Approved By:	RMG/Safety & Environmental Units
Issue/Revision Date	F.7.6.3183.B/ 2/8/08

Special Fire Fighting Procedures: Wear an approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

Unusual Fire Hazards: Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Vapors may form explosive mixtures with air in confined areas.

Hazardous Decomposition Products: Oxides of carbon, silicon and nitrogen and unknown materials.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill: Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed. Ventilate area. Cover with and inert absorbent material and collect into an appropriate container for disposal. Report spills and releases as required to appropriate authorities.

SECTION 7: HANDLING AND STORAGE

Handling: Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Always wear impervious gloves, chemical safety goggles and protective clothing when handling this material. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.

Storage: Store in a cool, dry, well-ventilated location away from incompatible materials. Keep containers closed when not in use.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
1-Methoxy-2-propanol	100 ppm TLV-TWA, 150 ppm TLV-STEL 100 ppm DFG MAK 100 ppm EU-TWA, 150 ppm EU-STEL skin
Additive	None Established
Water	None Established

Ventilation: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

Respiratory Protection: If needed, an approved respirator with organic vapor cartridges may be used. For higher exposures, a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Skin Protection: Impervious gloves are recommended. Based on available test data, 4H or Silver Shield gloves are suggested.

Eye Protection: Chemical safety goggles recommended.

Other Protective Equipment: Impervious clothing is recommended to prevent skin contact and contamination of personal clothing. An eye wash facility and safety shower should be available in the work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Liquid with a solvent odor.

pH: Not available

Boiling Point: 120°C

Vapor Pressure: 12.5 mmHg @ 25°C (PGME)

Vapor Density: 3.12 (PGME)

Flash Point: 32°C (90°F) (PGME)

Specific Gravity: Not available

Melting Point: Not Applicable

Water Solubility: Partially Soluble

Evaporation Rate: Not available

Flammable Limits: LEL: 0.8 vol % (Additive)
UEL: 10.9 vol % (PGME)

Prepared By:	Safety & Environmental Units
Approved By:	RMG/Safety & Environmental Units
Issue/Revision Date	F.7.6.3183.B/ 2/8/08

UN Number: UN3092
IATA Hazard Labels Required: Flammable Liquid

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: This product is not subject to reporting under CERCLA. Some states have more stringent reporting requirements. Report all spills in accordance with local, state and federal regulations.

SARA TITLE III:

Hazard Category for Section 311/312: Acute Health, Fire Hazard

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on TSCA.

STATE REGULATIONS:

California Proposition 65: This product contains the following substances known to the State of California to cause cancer and/or reproductive harm: None known

INTERNATIONAL REGULATIONS:

European Community Labeling:

	R10 Flammable S51 Use only in well ventilated areas.
--	---

SECTION 16: OTHER INFORMATION

HMIS Ratings: Health - 1 Flammability - 3 Reactivity - 0
NFPA Ratings: Health - 1 Flammability - 3 Reactivity - 0

SDS Revision History:

8/28/07: New SDS.

2/8/08: Updated format for REACH, updated wording for Carcinogen status, CERCLA, and California Proposition 65 statement, removed references to NIOSH, changed MSDS to SDS.

EU Classes and Risk Phrases for Reference (See Sections 2 and 3):

C Corrosive
R10 Flammable
R22 Harmful if swallowed.
R34 Causes burns.

=====

This above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Brewer Science shall not be held liable for any damage resulting from handling or from contact with the above product.

Prepared By:	Safety & Environmental Units
Approved By:	RMG/Safety & Environmental Units
Issue/Revision Date	F.7.6.3183.B/ 2/8/08